



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

22.08.03

REC'D 29 AUG 2003	
WIPO	PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02291520.1

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:  
Application no.: 02291520.1  
Demande no:

Anmeldetag:  
Date of filing: 18.06.02  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Koninklijke Philips Electronics N.V.  
Groenewoudseweg 1  
5621 BA Eindhoven  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Video encoding method and corresponding encoding and decoding devices

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

H04N7/26

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

**"VIDEO ENCODING METHOD AND CORRESPONDING ENCODING AND DECODING DEVICES"****FIELD OF THE INVENTION**

5                   The present invention relates to the field of video compression and, for instance, to the video coding standards of the MPEG family (MPEG-1, MPEG-2, MPEG-4) and the ITU-H.26X family (H.261, H.263 and extensions, H.26L). More specifically, this invention concerns an encoding method applied to a video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs) and generating, for coding all the video objects of  
10                   said scenes, a coded bitstream constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels.

                  The invention also relates to a corresponding encoding device, to a transmittable video signal consisting of a coded bitstream generated by such an encoding device, and to a  
15                   device for receiving and decoding a video signal consisting of such a coded bitstream.

**BACKGROUND OF THE INVENTION**

                  In the first video coding standards (up to MPEG-2 and H.263), the video is assumed to be rectangular and to be described in terms of a luminance channel and two chrominance channels. With MPEG-4, other channels have been introduced, the spatial  
20                   resolution of which is described at the sequence level (Video Object Layer, or VOL, in MPEG-4 terminology), as defined in the MPEG-4 document w3056, "Information Technology – Coding of audio-visual objects – Part 2 : Visual", ISO/IEC/JTC1/SC29/WG11, Maui, USA, December 1999. Only one description is given for all channels. The standard defines the "video\_object\_layer\_width" and "video\_object\_layer\_height" syntax elements (w3056, p.36 and  
25                   p.113), which are 13-bit unsigned integers representing the width and height of the displayable part of the luminance component in pixel units. From this values, the actual spatial resolution of the different channels is inferred as follows:

- the luminance channel spatial resolution is width x height;
- the shape channel spatial resolution is also width x height;
- 30                   - the chrominance channels spatial resolution is (width/2) x (height/2).

MPEG-4 also defines the so-called reduced resolution VOP tool. When this tool is used , the size of the macroblock used for motion compensation decoding is 32 x 32 pixels and the size of block is 16 x 16 pixels. It corresponds to the encoding of quarter resolution pictures (decimated by a factor of 2 vertically and horizontally) at the encoding side. The decoded pictures are then  
35                   up sampled to the normal resolution (width x height) at the decoding side. The standard has also additional syntax elements. A one bit-flag "reduced\_resolution\_vop\_enable", found at the VOL level (w3056, p.38 and p.118), indicates that the "Dynamic Resolution Conversion"(DRC)

tool is enabled when set to '1'. In such a case, the single bit flag "vop\_reduced\_resolution" has to be retrieved from every VOP header (w3056, p.41, p.47 and p.121). It signals whether the VOP is encoded at spatially reduced resolution or not. When this flag is set to '1', the VOP is encoded spatially reduced resolution and referred as Reduced Resolution VOP. When this flag is set to "0" or this flag is not present, the VOP is encoded in normal spatial resolution and shall be decoded by the normal decoding process. From these remarks, it can be seen that the spatial resolution of the picture is described at the VOP level, and unfortunately, all channels have to share the same description.

## SUMMARY OF THE INVENTION

It is therefore an object of the invention to propose a video coding method allowing to describe a video sequence with channels that have different resolutions.

To this end, the invention relates to a method such as defined in the introductory part of the description and which is moreover characterized in that said syntax comprises specific syntactic means for separately describing the spatial resolution of each channel.

The proposed solution, allowing to describe a video sequence with separate channels that have different characteristics, leads to a greater flexibility in digital video coding systems, such as the future H.26L standard.

In a more flexible solution, said syntactic means may even comprise, for each channel, specific syntactic elements for separately describing the spatial resolution of each image of the sequence (this solution may be optional), and this description may be given, for the current image of the input sequence, with respect to the spatial resolution of the previous image in the same channel.

For each channel and for each current image, said spatial resolution may moreover be described with respect to a reference (or nominal) spatial resolution, which is for instance a predetermined spatial resolution indicated at the beginning of the bitstream, or the spatial resolution of one of the channels. The spatial resolution will be preferably described by means of a division or a multiplication of said reference spatial resolution.

The invention also relates to a device for encoding a video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said device comprising means for structuring each scene of said sequence as a composition of video objects (VOs), means for coding the shape, the motion and the texture of each of said VOs, and means for multiplexing the coded elementary streams thus obtained into a single coded bitstream constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, said device being further characterized in that said multiplexing means comprise means for introducing into said single bitstream a specific information for separately describing the spatial resolution of each of said separate channels.

The invention also relates to a transmittable video signal consisting of a coded bitstream generated by an encoding method applied to a sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said coded bitstream, generated for coding all the video objects of said scenes, being constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, said signal being further characterized in that it includes a specific information for separately describing the spatial resolution of each of said separate channels.

The invention finally relates to a device for receiving and decoding a video signal consisting of a coded bitstream generated by an encoding method applied to a video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said coded bitstream, generated for coding all the video objects of said scenes, being constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, and moreover comprising a specific information for separately describing the spatial resolution of each of said separate channels, said decoding device being further characterized in that it includes means for reading in the received coded bitstream the specific spatial resolution of each of said separate channels.

#### **DETAILED DESCRIPTION OF THE INVENTION**

As said above, it is not possible, at that moment, to describe a video sequence with channels that have different resolutions. For instance, instead of having the classical quarter spatial resolution for the chrominance channels (decimated by a factor 2 in each direction), due to bitrate constraints, one could imagine to have a 9th resolution chrominance channels (decimated by a factor 3 in each direction). The solutions proposed here provide some syntax elements to support the lack of flexibility of current standards (to offer also more flexibility for future standards, the solution is extended to different channels, other than the luminance and chrominance ones, and proposes the reduced resolution channel tool).

In the following, it is assumed that the presence of channels is described by several syntax elements at the sequence level (VOL in MPEG-4 terminology), for instance as:

#### Channels presence description:

Video_object_layer_lum	1bit
Video_object_layer_chrom	1 bit (0 for black and white)
Video_object_layer_shape	1 bit (0 for rectangular)
number_of_additional_channels	4 bits
video_object_layer_additional_channel[0]	1 bit
video_object_layer_additional_channel[1]	1 bit

video\_object\_layer\_additional\_channel[i] 1 bit

.....

These syntax elements should be read as follows:

- if "Video\_object\_layer\_lum" is 1, it means that the bitstream contains syntax elements for a luminance channel ;
- if "Video\_object\_layer\_chrom" is 1, the bitstream contains syntax elements for the chrominance channels, else the sequence is assumed to be black and white ;
- if "Video\_object\_layer\_shape" is 1, the bitstream contains syntax elements to describe a non-rectangular shape for the picture, else it is assumed to be rectangular ;
- if "number\_of\_additional\_channels" is not zero, the bitstream contains syntax elements describing additional channels, which presence or not is described by video\_object\_layer\_additional\_channel[i] syntax element.

The following flags and syntax elements (in italic) are proposed to describe the spatial resolution and the availability of the reduced resolution tool of every channel. The basic idea is to start from a nominal resolution (the maximum resolution of all channels) and to express the spatial resolution of every channel in terms of ratios of this nominal size. At sequence high level description (equivalent to VOL MPEG-4 level), the following syntax elements are proposed :

**Table 1**

Element	Type	Semantic
<i>typical for Claim 1</i>		
<i>Vol_horiz_sampling_elements_lum</i>	Unsigned integer	Width of luminance channel in pixels
<i>Vol_vert_sampling_elements_lum</i>	Unsigned integer	Height of luminance channel in pixels
<i>Vol_horiz_sampling_elements_channels[i]</i>	Unsigned integer	Width of the i <sup>th</sup> additional channel
<i>Vol_vert_sampling_elements_channels[i]</i>	Unsigned integer	Height of the i <sup>th</sup> additional channel
<i>typical for Claim 2</i>		
<i>Vop_horiz_reduced_resolution_lum</i>	1 bit	Use the horizontal reduced resolution tool on the luminance channel
<i>Vop_vert_reduced_resolution_lum</i>	1 bit	Use the vertical reduced resolution tool on the luminance channel
<i>Vop_horiz_reduced_resolution_channels[i]</i>	1 bit	Use the horizontal reduced resolution tool on the i <sup>th</sup> additional channel
<i>Vop_vert_reduced_resolution_channels[i]</i>	1 bit	Use the vertical reduced resolution tool on the i <sup>th</sup> additional channel
<i>typical for Claim 3</i>		
<i>Vol_horiz_reduced_resolution_lum_enable</i>	1 bit	Enable the horizontal reduced resolution

		tool on the luminance channel
<i>Vol_vert_reduced_resolution_lum_enable</i>	1 bit	Enable the vertical reduced resolution tool on the luminance channel
<i>Vol_horiz_reduced_resolution_channels_enable[i]</i>	1 bit	Enable the horizontal reduced resolution tool on the $i^{\text{th}}$ additional channel
<i>Vol_vert_reduced_resolution_channels_enable[j]</i>	1 bit	Enable the vertical reduced resolution tool on the $j^{\text{th}}$ additional channel
<i>typical for Claim 6</i>		
<i>Vol_horiz_sampling_elements</i>	13 bits	Horizontal nominal size (pixels)
<i>Vol_vert_sampling_elements</i>	13 bits	Vertical nominal size (pixels)
<i>typical for Claim 8</i>		
<i>Vol_horiz_sampling_resolution_lum_ratio</i>	2 bits	Ratio between horizontal nominal size and luminance horizontal size
<i>Vol_vert_sampling_resolution_lum_ratio</i>	2 bits	Ratio between vertical nominal size and luminance vertical size
<i>Vol_horiz_sampling_resolution_channels_ratio[i]</i>	2 bits	Ratio between horizontal nominal size and $i^{\text{th}}$ additional channel horizontal size
<i>Vol_vert_sampling_resolution_channels_ratio[j]</i>	2 bits	Ratio between vertical nominal size and $j^{\text{th}}$ additional channel vertical size

5 The invention is obviously not limited to the encoding method thus defined . It also  
 relates to a device for encoding a video sequence corresponding to successive scenes  
 subdivided into successive video object planes (VOPs), said device comprising means for  
 structuring each scene of said sequence as a composition of video objects (VOs), means for  
 coding the shape, the motion and the texture of each of said VOs, and means for multiplexing  
 the coded elementary streams thus obtained into a single coded bitstream constituted of  
 encoded video data in which each data item is described by means of a bitstream syntax,  
 allowing to recognize and decode all the elements of the content of said bitstream, said content  
 10 being described in terms of separate channels, said device being further characterized in that  
 said multiplexing means comprise means for introducing into said single bitstream a specific  
 information for separately describing the spatial resolution of each of said separate channels.

15 The invention also relates to a transmittable video signal consisting of a coded  
 bitstream generated by an encoding method applied to a sequence corresponding to successive  
 scenes subdivided into successive video object planes (VOPs), said coded bitstream, generated  
 for coding all the video objects of said scenes, being constituted of encoded video data in which  
 each data item is described by means of a bitstream syntax allowing to recognize and decode  
 all the elements of the content of said bitstream, said content being described in terms of  
 separate channels, said signal being further characterized in that it includes a specific  
 20 information for separately describing the spatial resolution of each of said separate channels.

25 The invention finally relates to a device for receiving and decoding a video signal  
 consisting of a coded bitstream generated by an encoding method applied to a video sequence  
 corresponding to successive scenes subdivided into successive video object planes (VOPs), said  
 coded bitstream, generated for coding all the video objects of said scenes, being constituted of  
 encoded video data in which each data item is described by means of a bitstream syntax  
 allowing to recognize and decode all the elements of the content of said bitstream, said content

being described in terms of separate channels, and moreover comprising a specific information for separately describing the spatial resolution of each of said separate channels, said decoding device being further characterized in that it includes means for reading in the received coded bitstream the specific spatial resolution of each of said separate channels.



## CLAIMS :

1. An encoding method applied to an input video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs) and generating, for coding all the video objects of said scenes, a coded bitstream constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, said method being further characterized in that said syntax comprises specific syntactic means for separately describing the spatial resolution of each channel.
2. A method according to claim 1, characterized in that said syntactic means comprise, for each channel, specific syntactic elements for separately describing the spatial resolution of each image of the input sequence.
3. A method according to claim 2, characterized in that said separate description of the spatial resolution of each image of the input sequence is optional.
4. A method according to anyone of claims 2 and 3, characterized in that, for each channel, said syntactic means comprise syntactic elements for describing the spatial resolution of the current image of the input sequence with respect to the spatial resolution of the previous image in the same channel.
5. A method according to anyone of claims 2 to 4, characterized in that, for each channel and for each image, the spatial resolution is described with respect to a reference spatial resolution.
6. A method according to claim 5, characterized in that said reference spatial resolution is a predetermined spatial resolution indicated at the beginning of the bitstream.
7. A method according to claim 5, characterized in that said reference spatial resolution is the spatial resolution of one of the channels.
8. A method according to anyone of claims 5 to 7, characterized in that the spatial resolution is described by means of a division of said predetermined reference spatial resolution.
9. A method according to anyone of claims 5 to 7, characterized in that the spatial resolution is described by means of a multiplication of said predetermined reference spatial resolution.
10. A device for encoding a video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said device comprising means for structuring each scene of said sequence as a composition of video objects (VOs), means for coding the shape, the motion and the texture of each of said VOs, and means for multiplexing the coded elementary streams thus obtained into a single coded bitstream constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, said device being further characterized in that

said multiplexing means comprise means for introducing into said single bitstream a specific information for separately describing the spatial resolution of each of said separate channels.

5 11. A transmittable video signal consisting of a coded bitstream generated by an encoding method applied to a sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said coded bitstream, generated for coding all the video objects of said scenes, being constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, said  
10 signal being further characterized in that it includes a specific information for separately describing the spatial resolution of each of said separate channels.

12. A device for receiving and decoding a video signal consisting of a coded bitstream generated by an encoding method applied to a video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs), said coded bitstream, generated for coding all the video objects of said scenes, being constituted of encoded video data in which  
15 each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of the content of said bitstream, said content being described in terms of separate channels, and moreover comprising a specific information for separately describing the spatial resolution of each of said separate channels, said decoding device being further  
20 characterized in that it includes means for reading in the received coded bitstream the specific spatial resolution of each of said separate channels.

---

**Abstract**

The invention relates to an encoding method applied to a video sequence corresponding to successive scenes and generating a coded bitstream in which each data item is described by means of a bitstream syntax allowing, at the decoding side, to recognize and decode all the elements of the content of this coded bitstream. According to the invention, said syntax comprises specific syntactic means for separately describing the spatial resolution of each channel or, for each channel, the spatial resolution of each image of the input sequence. Moreover, said description may be done with respect to a reference spatial resolution, which may be either an absolute nominal spatial resolution or the spatial resolution of one of the channels. The invention also relates to the corresponding encoding device, transmittable video signal and decoding device.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**